

DATASHEET

GENERAL CHARACTERISTICS

Architecture	Client-server architecture
Configuration	Stand-alone or integrated solution

TECHNICAL SPECIFICATIONS

Multi-operator	Any number of clients may work at the same time
Server redundancy	Master / slave server with replication
Network redundancy	Both primary and secondary Internet connections
Sound	Optional sound when new alarm received
Privacy	Operators can only watch live cameras when intrusion detected
Activation of dissuasive devices	Remote relays such as sirens, lights, sprinklers, speakers, etc.
Audio	Bi-directional audio to communicate with intruders
Technical alarms	Network status, video analytics status, camera status
Bandwidth	Optimized for speed and bandwidth usage
3rd Party Software Integrations	Among others: MAstermind, Immix, Manitou, IBS-SBN, Sentinel, Patriot Systems, Azursost-Horus, Softguard, Sims, Avante, etc.
Verification support	Integrated PTZ Preset

SERVER REQUIREMENTS

Processor	Intel Pentium Dual Core or higher
Memory (RAM)	4.00 GB or better
Hard disk	160 GB for OS and application
Operating system	Microsoft Windows Server 2003 32-bit Microsoft Windows 7 Pro 32-bit / 64-bit Microsoft Windows 8 Professional or Enterprise Microsoft Windows 10 Professional or Enterprise More options available upon request
Internet connection	RJ45 network connector 100/1000 Mbps
Database engine	SQL SERVER 2012 Express
Hardware	Dedicated machine (physical or virtual)